


# **Model 915 Time & Attendance Terminals**

Choice of Proximity Barcode, Magnetic Stripe, or Fingerprint Reader in an Improved, Intuitive, Compact Design







BC-915 Barcode Card Reader



MG-915 Magnetic Card Reader



Bio915-125 / Bio915-HID Fingerprint Reader

## **Standard Functions**

- Wi-Fi Standard Feature on All Devices
- User-Friendly UI and Menu Design
- Hardware-Level Clock Data Input Authentication
- User Level Duplicate Punch Prevention
- Multiple Level Job Code Entry Support
- Automatic Status Key Switch
- Supports up to 9 Digit User ID
- Daylight Savings Time Support
- · Customizable Bell Schedules
- USB-Host Port Provided

## **Terminal Specifications**

#### Capacity

ID Cards: up to 10,000 Transactions: up to 100,000 Fingerprint templates: 3,000

**Fingerprint Sensor** 

Optical

Display

3.0 in. TFT Color Screen

### Communications

Ethernet, USB-Host, Wi-Fi

#### Power

12 V DC, 1.5 A

Optional: 12V POE injector (sold separately)
Optional: 12V Battery Backup (sold separately)

#### Environment

Operating Temperature: 32° F to 113° F (0° C to 45° C)

Operating Humidity: 5% to 80%

### **Supported Devices**

Bio915-125 Fingerprint and RFID prox reader Bio915-HID Fingerprint and HID prox reader

MG-915 Magnetic card reader BC-915 Barcode card reader

Prox915-125 Standard RFID prox reader

#### Dimensions

Width: 6.5 in. (16.5 cm) Height: 5.5 in. (14 cm) Depth: 1.8 in. (4.6 cm) Weight: 0.95 lbs. (0.43 kg)